

TECHNICAL DATASHEET

GROUP: COPOLYMER – PAINT IND.

SCALE CHEMICALS REF.: V2 REV. DT: 20/10/2022 CATEGORY: TEL: 00961 70221782 **PVA COPOLYMER** EMAIL: INFO@SCALECHEMICALS.COM **VAM-VEOVA** WEB: WWW.SCALECHEMICALS.COM PRODUCT NAME: Pv

DESCRIPTION: WATER BASED PLASTICIZED COPOLYMER EMULSION (PVA) **PHENOL FREE**

 APPLICATION: CAN BE USED FOR PRODUCING SUPERIOR QUALITY PAINT AND GIVES HIGH TENSILE STRENGTH WITH SUPERIOR SHEAR STABILITY BEST FOR OUTDOOR AND INDOOR PAINT AS WELL AS TEXTURED COATING 	
SPECIFICATION / CHARACTERISTIC / FEATURE	DATA / VALUE
CHEMICAL COMPOSITION	POLYVINYL ACETATE EMULSION - COPOLYMER
EMULSIFYING SYSTEM	FREE PHENOL ETHOXYLATE
PHYSICAL APPEARANCE	MILKY WHITE EMULSION
SOLID CONTENT	50 (+/- 2%)
VISCOSITY @20°C RH #6 RPM 4,8	~30P
DENSITY	~1.1KG
PH	4~6
MFFT	4°C (APPROX)
PLASTICIZER	2,2,4-TRIMETHYL-1,3-PENTANDIOL MONOISOBUTYRATE
MECHANICAL & HIGH TEMPERATURE STABILITY, RESISTANCE TO AIR & HUMIDITY, TENSILE	EXCELLENT
PACKAGING	50KG, 125KG, 150KG, 1000KG
HANDLING & STORAGE	TO BE STORED IN SEALED CONTAINERS IN DRY CONDITION, AWAY FROM DIRECT HEAT, DUST, SUN LIGHT & MOISTURE. PROTECT FROM FROST. CONTAINERS ONCE OPENED SHOULD BE SHUT TIGHTLY TO PREVENT CONTAMINATION. A FILTRATION OR SIEVE PROCESS IS RECOMMENDED BEFORE FURTHER PROCESSING. FOR BULK STORAGE, REGULAR STIRRING IS SUGGESTED. FOR IBC OR DRUMS, PRODUCT TENDS TO FILM ON THE TOP OF THE SURFACE OF THE PACKAGING, THEREFORE IT SHOULD BE STORED INDOOR, AVOIDING DIRECT SUNLIGHT AND CAREFULLY TRANSPORTED
SHELF LIFE	18 MONTHS FROM DATE OF MANUFACTURE IF STORED AND TRANSPORTED HYGIENICALLY, AVOIDING FROST AND DIRECT SUNLIGHT