

TECHNICAL DATA SHEET

SCALE CHEMICALS REF.: TDS-05 **Rev. Dt: 10/11/2021**

TEL: 00961 70 221782

EMAIL: lnfo@scalechemicals.com
WEB: www.scalechemicals.com

PVA HOMOPOLYMER EMULSION

PRODUCT NAME:

CATEGORY:

GROUP: POLYMER EMULSION

DESCRIPTION: WATER BASED PLASTICIZED POLYVINYL ACETATE (PVA) HOMOPOLYMER EMULSION STABILIZED WITH POLYVINYL ALCOHOL.

APPLICATION:

CAN BE USED FOR PRODUCING SUPERIOR QUALITY WOOD, BUILDING ADHESIVES AND GIVES HIGH TENSILE STRENGTH
WITH SUPERIOR SHEAR STABILITY. FAST DRY AND BEST USED FOR COLD CLIMATE

WITH SUPERIOR SHEAR STABILITY. FAST DRY AND BEST USED FOR COLD CLIMATE	
SPECIFICATION / CHARACTERISTIC / FEATURE	DATA / VALUE
CHEMICAL COMPOSITION	POLYVINYL ACETATE EMULSION
EMULSIFYING SYSTEM	POLYVINYL ALCOHOL
PHYSICAL APPEARANCE	MILKY YELLOW EMULSION
SOLID CONTENT	46 (+/- 2%)
VISCOSITY @20°C RH #6	40000 cp
DENSITY	~1.1kg
РН	4 ~ 6
MFFT	<4°C
PLASTICIZER	2,2,4-TRIMETHYL-1,3-PENTANDIOL MONOISOBUTYRATE
MECHANICAL & HIGH TEMPERATURE STABILITY, RESISTANCE TO AIR & HUMIDITY, TENSILE	EXCELLENT
PACKAGING	4KG, 10KG, 20KG, 50KG, 1000KG
HANDLING & STORAGE	TO BE STORED IN SEALED CONTAINERS IN DRY CONDITION, AWAY FROM DIRECT HEAT, DUST, SUN LIGHT & MOISTURE. PROTECT FROM FROST. CONTAINERS ONCE OPENED SHOULD BE SHUT TIGHTLY TO PREVENT CONTAMINATION
SHELF LIFE	18 MONTHS FROM DATE OF MANUFACTURE IF STORED AND TRANSPORTED HYGIENICALLY, AVOIDING FROST AND DIRECT SUNLIGHT